



快插接头 FOR THE FOOD INDUSTRY SERIES F-NSF PLUS

Excellent pipe retention, easy release.
Entirely in 黄铜. NSF certificate and EU compliant.



螺纹口	公制或 G (BSP): M5 - 1/2"
°	Ø4 - Ø10 mm
☒	-20 / +150°C
☒	☒ - 16 bar
ypP☒	PTFE



y ☒ ☒ h, ☒ NSF certificate and EU compliant.



☒	☒ G (BSP): M5 - 1/2"
°	Ø4 - Ø12 mm
☒	-20 / +150°C
☒	☒ - 18 bar
ypP☒	PTFE



STANDARD FITTINGS SERIES A - XA

For various industrial uses. In nickel-plated ☒ Aisi 316 L



☒	☒ (BSP): M5 - 3/4" (A) G (BSP): 1/8" - 1/2" (XA)
☒	☒ /steel limits
☒	☒ b - 60 bar (A) - 真空 - 200 bar (XA)



COMPRESSION FITTINGS SERIES B

Strong retention.

☒	G (BSP): 1/8" - 1/2"
°	Ø4/2 - Ø15/12
☒	Pipe limits
☒	真空 - 60 bar
建议使用的气管	Copper



QUICK FITTINGS SERIES C - XC

Strong retention. No air loss. In nickel-plated 黄铜 or Aisi 316 L.



螺纹口	G (BSP): 1/8" - 1/2" (C) - G (BSP): 1/8" - 3/8" (XC)
直径	Ø4/2 - Ø15/12 (C) - Ø6/4 - Ø10/8 (XC)
温度	Pipe limits
压力	真空 - 18 bar (C) - 真空 - 25 bar (XC)
建议使用的气管	PA11, PA12, PTFE



BANJO FITTINGS SERIES D

Strong retention. No air loss.

☒	☒ G (BSP): M5 - 1/2"
°	Ø4 - Ø12 mm
☒	Pipe limits
☒	☒ - 18 bar
ypP☒	PA11, PA12, PTFE



Corporate website